

Hydronix In-Line Mineralizer Installation Manual



Thank you for choosing the Hydronix In-Line Mineralizer. This installation manual will guide you through the process step by step. Please read the entire guide before starting the installation to ensure a smooth setup

Requirements:

- 3/8" water supply line (included either existing on your current undersink system or with purchase of Hydronix In-Line Mineralizer

Installation Steps:

Step 1: Preparation

- 1. Turn off the water supply to your undersink filter system.
- 2. Open faucet or spigot to relieve pressure on tubing and system
- 3. Place a towel or cloth beneath the installation area to catch any water drips.

Step 2: Identify Installation Point

- 1. Choose a suitable location on the water supply line of your undersink filter system for installing the mineralizer.
- 2. The mineralizer should be set up on the 3/8" tubing *after* the filter stages and *before* the faucet to ensure optimal water quality.

Step 3: Install Mineralizer

- 1. Locate the pre-installed push-connect fittings on the Hydronix In-Line Mineralizer.
- 2. Identify the inlet (water source) and outlet (water destination) sides of the mineralizer.
- 3. Make a straight cut through the 3/8" tubing and ensure there are no rough edges, ensure the cut is not angled as this will result in leaking from the push connect.
- 4. Insert the 3/8" water supply line directly into the inlet push-connect fitting until it clicks securely into place.
- 5. Insert the other end of the mineralizer's outlet side into the water line leading to your faucet. Ensure a firm connection by feeling for the click.
- 6. Place blue or red safety clips onto each push connect fitting

Step 4: Turn On Water Supply

- 1. Gradually turn on the water supply to your undersink filter system.
- 2. Check the fittings and connections for any signs of leaks. If you observe any leaks, turn off the water supply and recheck the fittings for proper insertion.

Step 5: Flushing the System

- 1. Run water through the mineralizer and out of the faucet for a few minutes to flush out air bubbles and any loose particles that might have entered during installation.
- 2. This step will help prime the mineralizer and ensure its proper functioning.

Step 6: Final Check

- 1. Once the system has been flushed and there are no leaks, your installation is complete.
- 2. Keep an eye on the mineralizer over the next few days to ensure that everything is functioning as intended.

Congratulations! You have successfully installed the Hydronix In-Line Mineralizer onto your undersink filter system. Enjoy the benefits of mineralized water in your home.

If you encounter any issues during installation, please contact 208-462-0626 or email zach@greenfieldwater.com

